



PIN	A±0.20	B±0.25	C±0.20	D±0.38
6	5.08	16.76	22.86	26.92
8	7.62	19.30	25.40	29.46
10	10.16	21.84	27.94	32.00
14	15.24	26.92	33.02	37.08
16	17.78	29.46	35.56	39.62
20	22.86	34.54	40.64	44.70
24	27.94	39.62	45.72	49.78
26	30.48	42.16	48.26	52.32
30	35.56	47.24	53.34	57.40
34	40.64	52.32	58.42	62.48
40	48.26	59.94	66.04	70.10
50	60.96	72.64	78.74	82.80
60	73.66	85.35	91.44	95.50
64	78.74	90.42	96.52	100.58

NOTES:

- MATERIALS:
 - INSULATOR: Polyester UL94V-0.
 - CONTACT: Copper ALLOY.
 - PLATED: CONTACT GOLD PLATED OVER Ni.
- ELECTRICAL CHARACTERISTICS:
 - CURRENT RATING: 3 Amp.
 - CONTACT RESISTANCE: 20 mohms Max.
 - WITHSTANDING VOLTAGE: 500V AC Min.
 - INSULATION RESISTANCE: 1000 MOhms Min.
 - Operation Temperature: -40° C~+105° C.
- Only 64P with three key. Others with one key.
- 6~16Pin no window, Others with two windows.

Part NO.

230-0*0-***-2**

Solder length
Dim "L"
1:3.4
7:4.5

Marks
2:G/F
0:Nextron
9:Autl. 0~2u"
A:None

Housing Color
0:Black (PBT)
8:Grey (PBT)
C:Black (PA9T)

NO. Of Positions
6~64

X ±0.5	UNITS	NAME:
X ±0.38	mm	xxPIN 2.54mm
.XX±0.25	MAT'L	EJECTOR HEADER CONNECTOR
.XXX±0.08	FINISH	PART NO.:
'X' ±2'	APPD:	SEE TABLE
	CHKD:	09/17'25
	DR:	niezhengqi
		09/17'25

深圳市君灏精密工业有限公司		DWG NO.:	EP-C-230-0200-0017
SHENZHEN JUNHAO ENGINEERING CO., LTD		SCALE	SHEET
TITLE: 2.54mm EJECTOR HEADER STRAIGHT Type		1:1	1/1
		REV.	B1

REV.	ECN NO.	APPD	DATE
A0	RELEASE	Cheng	08/09/05
A1	底部胶脚上增加防刮槽	Cheng	08/23/11
A2	图面更新	niezhengqi	04/20/17
B0	增加图上的说明	niezhengqi	10/18/18
B1	电镀规格更新	niezhengqi	09/17/25

PCB LAYOUT