

PCB LAYOUT

NOTES:
 1. MATERIALS:
 1-1. INSULATOR: Polyester UL94V-0.
 1-2. CONTACT: BRASS.
 1-3. PLATED: CONTACT GOLD PLATED OVER NI.
 2. ELECTRICAL CHARACTERISTICS:
 2-1. CURRENT RATING: 1.0 Amp.
 2-2. VOLTAGE RATING: 250V AC/DC.
 2-3. CONTACT RESISTANCE: 20 mOhms MAX.
 2-4. INSULATION RESISTANCE: 1000 MOhms MIN.
 2-5. WITHSTANDING VOLTAGE: 500V AC/MINUTE.
 2-6. Operation Temperature: -40° C~+105° C.

Part NO.

210-***2*-*02*-***


NO. Of Positions: 04 80
 Contact Length: Dim "A" X "B"
 1: 2.8x4.0
 R/A Hight: Plated
 Dim C: 1:0.25
 2:1.0
 3:1.5
 Housing Color: 0:BLACK 9:WHITE
 Housing Material: 4:PA6T

See Table (1)

Code	Definition
1	Gold Flash
2	Gold 1.0~2u"

X ±0.5	UNITS	mm	NAME:	2.0 Pin Header Double Row
.X ±0.30	MAT'L		PART NO.:	210-***2*-*02*-***
.XX±0.20	FINISH		APPD:	jeff
.XXX±0.10			CHKD:	jeff
.X' ±2'			DR:	niezhenqi
			DATE:	09/17/25
THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF JUNIAO ENGINEERING CO., LTD. ANY REPRODUCTION OR USE IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF JUNIAO ENGINEERING CO., LTD. IS STRICTLY PROHIBITED.				
			TITLE:	2.0 Pin Header Double Row R/A Type
			DWG NO.:	EP-C-210-0020-0134
SCALE		SHEET	REV.	
1:1		1/1	A2	

深圳市君灏精密工业有限公司
 SHENZHEN JUNIAO ENGINEERING CO., LTD



1 2 3 4 5 6 7 8