



PCB LAYOUT

Table (1)

Code	Definition
1	Gold/Flash
2	Gold 1.0~2u"

- NOTES:
- MATERIALS:
 - INSULATOR: Polyester UL94V-0.
 - CONTACT: BRASS.
 - PLATED: CONTACT GOLD PLATED OVER NI.
 - ELECTRICAL CHARACTERISTICS:
 - CURRENT RATING: 3 Amp.
 - VOLTAGE RATING: 250V AC/DC.
 - CONTACT RESISTANCE: 20 mOhms MAX.
 - INSULATION RESISTANCE: 1000 MOhms MIN.
 - WITHSTANDING VOLTAGE: 500V AC/MINUTE.
 - Operation Temperature: -40° C~+105° C.

Part NO.
213-***1*-002*-***

- NO. Of Positions: 04~80
 - Contact length: "A"X"B"
 - Dim "A"X"B"
 - 1: 3.0x6.0
 - 2: 2.4x6.0
 - 3: 4.5x6.0
 - 5: 3.0x4.5
 - 7: 3.2x5.84
 - 8: 3.0x10.0
 - W: 3.0x3.0
- Housing Color
 0: BLACK 9: WHITE
 Housing Material
 0: PBT 4: PA6T
 Plated
 See Table (1)

X ±0.5		UNITS		NAME:	
.X ±0.38	mm	2.54mm Pin Header Double Row			
.XX±0.25	MAT'L	PART NO.:		SHENZHEN JUNHAO ENGINEERING CO., LTD	
.XXX±0.08	FINISH	213-***1*-002*-***			
.X' ±2"		APPD:	jeff	09/1725	
		CHKD:	jeff	09/1725	
		DR:	niezhenqi	09/1725	
		DWG NO.:		EP-C-213-0010-0140	
		TITLE:		2.54mm Pin Header Double Row Straight Pin	
		SCALE	SHEET	REV.	
		1:1	1/1	A1	

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF JUNHAO ENGINEERING CO., LTD. AND SHOULD BE KEPT IN CONFIDENTIALITY. NO PART OR PORTION THEREOF SHOULD BE REPRODUCED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF JUN HAO ENGINEERING CO.,LTD